

R404A

A-Gas (Australia) Pty Ltd

Version No: 10.1

Safety Data Sheet according to Work Health and Safety Regulations (Hazardous Chemicals) 2023 and ADG requirements

Issue Date: **28/05/2024**Print Date: **02/07/2024**

L.GHS.AUS.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	R404A			
Synonyms	Suva HP62; 404A; Suva 404A; Suva R404A; HP62			
Proper shipping name	REFRIGERANT GAS R 404A			
Chemical formula	Not Applicable			
Other means of identification	Not Available			

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Refrigerant, for professional users only The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation.
--------------------------	--

Details of the manufacturer or supplier of the safety data sheet

Registered company name	A-Gas (Australia) Pty Ltd				
Address	9-11 Oxford Rd, Laverton North Victoria 3026 Australia				
Telephone	93689222				
Fax	Not Available				
Website	www.agas.com				
Email	Not Available				

Emergency telephone number

Association / Organisation	A-Gas (Australia) Pty Ltd	CHEMWATCH EMERGENCY RESPONSE (24/7)		
Emergency telephone numbers	1800737001	+61 1800 951 288		
Other emergency telephone numbers	Not Available	+61 3 9573 3188		

Once connected and if the message is not in your preferred language then please dial 01

SECTION 2 Hazards identification

Classification of the substance or mixture

Poisons Schedule	Not Applicable
Classification ^[1]	Gases Under Pressure (Liquefied Gas)
Legend:	1. Classification by vendor; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

Label elements

Hazard pictogram(s)



Signal word

Warning

Page 2 of 11 R404A Issue Date: **28/05/2024**Print Date: **02/07/2024**

Hazard statement(s)

H280	Contains gas under pressure; may explode if heated.	
AUH044	Risk of explosion if heated under confinement.	

Precautionary statement(s) General

P101	If medical advice is needed, have product container or label at hand.		
P102	Keep out of reach of children.		
P103	Read carefully and follow all instructions.		

Precautionary statement(s) Prevention

Not Applicable

Precautionary statement(s) Response

Not Applicable

Precautionary statement(s) Storage

P410+P403

Protect from sunlight. Store in a well-ventilated place.

Precautionary statement(s) Disposal

Not Applicable

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight] Name				
420-46-2	30-60 <u>1,1,1-trifluoroethane</u>				
354-33-6	30-60 <u>pentafluoroethane</u>				
811-97-2	<10 <u>1,1,1,2-tetrafluoroethane</u>				
Legend: 1. Classification by vendor; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available					

SECTION 4 First aid measures

Description of first aid measures

- If product comes in contact with eyes remove the patient from gas source or contaminated area.
- ▶ Take the patient to the nearest eye wash, shower or other source of clean water.
- Open the eyelid(s) wide to allow the material to evaporate.
- Gently rinse the affected eye(s) with clean, cool water for at least 15 minutes. Have the patient lie or sit down and tilt the head back. Hold the eyelid(s) open and pour water slowly over the eyeball(s) at the inner corners, letting the water run out of the outer corners.
- The patient may be in great pain and wish to keep the eyes closed. It is important that the material is rinsed from the eyes to prevent further damage.

Eye Contact

- Ensure that the patient looks up, and side to side as the eye is rinsed in order to better reach all parts of the eye(s)
- ► Transport to hospital or doctor.
- Even when no pain persists and vision is good, a doctor should examine the eye as delayed damage may occur.
- If the patient cannot tolerate light, protect the eyes with a clean, loosely tied bandage.
- ▶ Ensure verbal communication and physical contact with the patient.

 $\ensuremath{\text{\textbf{DO NOT}}}$ allow the patient to rub the eyes

DO NOT allow the patient to tightly shut the eyes

DO NOT introduce oil or ointment into the eye(s) without medical advice

DO NOT use hot or tepid water.

Skin Contact

If skin contact occurs:

- ▶ Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

In case of cold burns (frost-bite):

- ▶ Move casualty into warmth before thawing the affected part; if feet are affected carry if possible
- ▶ Bathe the affected area immediately in luke-warm water (not more than 35 deg C) for 10 to 15 minutes, immersing if possible and without rubbing
- ▶ **DO NOT** apply hot water or radiant heat.
- ▶ Apply a clean, dry, light dressing of "fluffed-up" dry gauze bandage
- ▶ If a limb is involved, raise and support this to reduce swelling

Version No: 10.1 Page 3 of 11 Issue Date: 28/05/2024 Print Date: 02/07/2024

R404A

	 If an adult is involved and where intense pain occurs provide pain killers such as paracetomol Transport to hospital, or doctor Subsequent blackening of the exposed tissue indicates potential of necrosis, which may require amputation.
Inhalation	 Following exposure to gas, remove the patient from the gas source or contaminated area. NOTE: Personal Protective Equipment (PPE), including positive pressure self-contained breathing apparatus may be required to assure the safety of the rescuer. Prostheses such as false teeth, which may block the airway, should be removed, where possible, prior to initiating first aid procedures. If the patient is not breathing spontaneously, administer rescue breathing. If the patient does not have a pulse, administer CPR. If medical oxygen and appropriately trained personnel are available, administer 100% oxygen. Summon an emergency ambulance. If an ambulance is not available, contact a physician, hospital, or Poison Control Centre for further instruction. Keep the patient warm, comfortable and at rest while awaiting medical care. MONITOR THE BREATHING AND PULSE, CONTINUOUSLY. Administer rescue breathing (preferably with a demand-valve resuscitator, bag-valve mask-device, or pocket mask as trained) or CPR if necessary.
Ingestion	 Not considered a normal route of entry. For advice, contact a Poisons Information Centre or a doctor. Avoid giving milk or oils. Avoid giving alcohol.

Indication of any immediate medical attention and special treatment needed

for intoxication due to Freons/ Halons;

A: Emergency and Supportive Measures

- Maintain an open airway and assist ventilation if necessary
- Treat coma and arrhythmias if they occur. Avoid (adrenaline) epinephrine or other sympathomimetic amines that may precipitate ventricular arrhythmias. Tachyarrhythmias caused by increased myocardial sensitisation may be treated with propranolol, 1-2 mg IV or esmolol 25-100 microgm/kg/min IV.
- ▶ Monitor the ECG for 4-6 hours
- B: Specific drugs and antidotes:
 - ▶ There is no specific antidote
- C: Decontamination
- Inhalation; remove victim from exposure, and give supplemental oxygen if available.
- Ingestion; (a) Prehospital: Administer activated charcoal, if available. DO NOT induce vomiting because of rapid absorption and the risk of abrupt onset CNS depression. (b) Hospital: Administer activated charcoal, although the efficacy of charcoal is unknown. Perform gastric lavage only if the ingestion was very large and recent (less than 30 minutes)
- D: Enhanced elimination:
- There is no documented efficacy for diuresis, haemodialysis, haemoperfusion, or repeat-dose charcoal.

POISONING and DRUG OVERDOSE, Californian Poison Control System Ed. Kent R Olson; 3rd Edition

- Do not administer sympathomimetic drugs unless absolutely necessary as material may increase myocardial irritability.
- No specific antidote
- Because rapid absorption may occur through lungs if aspirated and cause systematic effects, the decision of whether to induce vomiting or not should be made by an attending physician.
- If lavage is performed, suggest endotracheal and/or esophageal control.
- Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach.
- Treatment based on judgment of the physician in response to reactions of the patient

For gas exposures:

BASIC TREATMENT

- Establish a patent airway with suction where necessary.
- Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- Administer oxygen by non-rebreather mask at 10 to 15 l/min.
- Monitor and treat, where necessary, for pulmonary oedema .
- Monitor and treat, where necessary, for shock.
- Anticipate seizures.

ADVANCED TREATMENT

- Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- Positive-pressure ventilation using a bag-valve mask might be of use.
- Monitor and treat, where necessary, for arrhythmias.
- Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.
- Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- Treat seizures with diazepam.
- Proparacaine hydrochloride should be used to assist eye irrigation.

BRONSTEIN, A.C. and CURRANCE, P.L.

EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

SECTION 5 Firefighting measures

Page 4 of 11 R404A Issue Date: 28/05/2024 Print Date: 02/07/2024

Extinguishing media

 $\textbf{SMALL FIRE:} \ \textbf{Use extinguishing agent suitable for type of surrounding fire.}$

LARGE FIRE: Cool cylinder.

DO NOT direct water at source of leak or venting safety devices as icing may occur.

Special hazards arising from the substrate or mixture

Fire Incompatibility Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Advice for firefighters

	GENERAL			
Fire Fighting	Alert Fire Brigade and tell them location and nature of hazard.			
	 Wear breathing apparatus and protective gloves. 			
	Fight fire from a safe distance, with adequate cover.			
	Use water delivered as a fine spray to control fire and cool adjacent area.			
	► Containers may explode when heated - Ruptured cylinders may rocket			
	 Fire exposed containers may vent contents through pressure relief devices. 			
	 High concentrations of gas may cause asphyxiation without warning. 			
	May decompose explosively when heated or involved in fire.			
	Contact with gas may cause burns, severe injury and/ or frostbite.			
Fire/Explosion Hazard	Decomposition may produce toxic fumes of:			
	carbon monoxide (CO)			
	carbon dioxide (CO2)			
	hydrogen fluoride			
	other pyrolysis products typical of burning organic material.			
	Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions.			
HAZCHEM	2TE			

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Avoid breathing vapour and any contact with liquid or gas. Protective equipment including respirator should be used. DO NOT enter confined spaces where gas may have accumulated. Increase ventilation.
Major Spills	 Clear area of all unprotected personnel and move upwind. Alert Emergency Authority and advise them of the location and nature of hazard. Wear breathing apparatus and protective gloves. Prevent by any means available, spillage from entering drains and water-courses. Remove leaking cylinders to a safe place. Fit vent pipes. Release pressure under safe, controlled conditions Burn issuing gas at vent pipes. DO NOT exert excessive pressure on valve; DO NOTattempt to operate damaged valve.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

· Consider use in closed pressurised systems, fitted with temperature, pressure and safety relief valves which are vented for safe dispersal. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature

- · The tubing network design connecting gas cylinders to the delivery system should include appropriate pressure indicators and vacuum or suction lines.
- · Fully-welded types of pressure gauges, where the bourdon tube sensing element is welded to the gauge body, are recommended.
- · Before connecting gas cylinders, ensure manifold is mechanically secure and does not containing another gas.
- ▶ **DO NOT** transfer gas from one cylinder to another.

Other information

Safe handling

- Cylinders should be stored in a purpose-built compound with good ventilation, preferably in the open.
- ▶ Such compounds should be sited and built in accordance with statutory requirements.
- ► The storage compound should be kept clear and access restricted to authorised personnel only.
- Cylinders stored in the open should be protected against rust and extremes of weather.

DO NOT store above 50 deg. C.

Page 5 of 11 R404A

Issue Date: 28/05/2024 Print Date: 02/07/2024

Conditions for safe storage, including any incompatibilities

Suitable container

- Cylinder:
- Ensure the use of equipment rated for cylinder pressure.
- Ensure the use of compatible materials of construction.
- Valve protection cap to be in place until cylinder is secured, connected.
- Cylinder must be properly secured either in use or in storage.
- Storage incompatibility
- Avoid reaction with oxidising agents
- Avoid magnesium, aluminium and their alloys, brass and steel.















Must not be stored together

- May be stored together with specific preventions
- May be stored together

Note: Depending on other risk factors, compatibility assessment based on the table above may not be relevant to storage situations, particularly where large volumes of dangerous goods are stored and handled. Reference should be made to the Safety Data Sheets for each substance or article and risks assessed accordingly.

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	1,1,1,2-tetrafluoroethane	1,1,1,2-Tetrafluoroethane	1000 ppm / 4240 mg/m3	Not Available	Not Available	Not Available

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
1,1,1,2-tetrafluoroethane	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
1,1,1-trifluoroethane	Not Available	Not Available
pentafluoroethane	Not Available	Not Available
1,1,1,2-tetrafluoroethane	Not Available	Not Available

MATERIAL DATA

Exposure controls

Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

Individual protection measures, such as personal protective equipment









Eye and face protection

- Safety glasses with side shields.
- ► Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.

Skin protection

See Hand protection below

- When handling sealed and suitably insulated cylinders wear cloth or leather gloves.
- ► Insulated gloves: Hands/feet protection
 - ▶ NOTE: Insulated gloves should be loose fitting so that may be removed quickly if liquid is spilled upon them. Insulated gloves are not made to permit hands to be placed in the liquid; they provide only short-term protection from accidental contact with the liquid.

Body protection

See Other protection below

Other protection

- Protective overalls, closely fitted at neck and wrist.
- Eye-wash unit.
- Ensure availability of lifeline in confined spaces.

Page 6 of 11 R404A Issue Date: **28/05/2024**Print Date: **02/07/2024**

Staff should be trained in all aspects of rescue work.

Respiratory protection

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Colourless liquefied gas with slight ether-like odour		
Physical state	Liquified Gas	Relative density (Water = 1)	1.044 @ 25 deg C
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Applicable
pH (as supplied)	~7	Decomposition temperature (°C)	728
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	-46.2	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	1254.6 @ 25 C, 2310 @ 50 deg C	Gas group	Not Available
Solubility in water	Not Available	pH as a solution (1%)	Not Applicable
Vapour density (Air = 1)	3.4 @ 25 deg C	VOC g/L	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur. Extremely high temperatures.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled

Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.

Limited evidence or practical experience suggests that the material may produce irritation of the respiratory system, in a significant number of individuals, following inhalation. In contrast to most organs, the lung is able to respond to a chemical insult by first removing or neutralising the irritant and then repairing the damage. The repair process, which initially evolved to protect mammalian lungs from foreign matter and antigens, may however, produce further lung damage resulting in the impairment of gas exchange, the primary function of the lungs. Respiratory tract irritation often results in an inflammatory response involving the recruitment and activation of many cell types, mainly derived from the vascular system.

Common, generalised symptoms associated with non-toxic gas inhalation include :

- central nervous system effects such as headache, confusion, dizziness, progressive stupor, coma and seizures;
- respiratory system complications may include tachypnoea and dyspnoea;
- cardiovascular effects may include circulatory collapse and arrhythmias;
- gastrointestinal effects may also be present and may include mucous membrane irritation and nausea and vomiting.

Material is highly volatile and may quickly form a concentrated atmosphere in confined or unventilated areas. The vapour may displace and replace air in breathing zone, acting as a simple asphyxiant. This may happen with little warning of overexposure.

The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation.

R404A

Issue Date: **28/05/2024**Print Date: **02/07/2024**

		use dermal problems due to a tendency to remove natural oils from the		
Ingestion	skin causing irritation and the development of dry, sensitive skin. They do not appear to be appreciably absorbed. Overexposure is unlikely in this form. Not normally a hazard due to physical form of product. Considered an unlikely route of entry in commercial/industrial environments			
Skin Contact	Limited evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis. Vapourising liquid causes rapid cooling and contact may cause cold burns, frostbite, even through normal gloves. Frozen skin tissues are painless and appear waxy and yellow. Signs and symptoms of frost-bite may include "pins and needles", paleness followed by numbness, a hardening an stiffening of the skin, a progression of colour changes in the affected area, (first white, then mottled and blue and eventually black; on recovery, red, hot, painful and blistered). Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.			
Еуе	Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn). Vapourising liquid causes rapid cooling and contact may cause cold burns, frostbite, even through normal gloves. Frozen skin tissues are painless and appear waxy and yellow. Signs and symptoms of frost-bite may include "pins and needles", paleness followed by numbness, a hardening an stiffening of the skin, a progression of colour changes in the affected area, (first white, then mottled and blue and eventually black; on recovery, red, hot, painful and blistered).			
Chronic	these have not been verified by current research. The high incidence	nologic lesions of the liver and other visceral organs in experimental tilluorocarbons may cause leukemia, cancer, sterility and birth defects; of cancer, spontaneous abortion and congenital anomalies amongst il anaesthetics, has caused some scientists to call for a lowering of the		
R404A	Not Available	IRRITATION Not Available		
	тохісіту	IRRITATION		
1,1,1-trifluoroethane	Inhalation (Rat) LC50: >540000 ppm4h ^[2]	Not Available		
	тохісіту	IRRITATION		
pentafluoroethane	Inhalation (Rat) LC50: >709000 ppm4h ^[2]	Eye: no adverse effect observed (not irritating) ^[1]		
		Skin: no adverse effect observed (not irritating) $^{[1]}$		
	тохісіту	IRRITATION		
	Inhalation (Rat) LC50: 359453.102 ppm4h ^[2]	Eye: adverse effect observed (irritating) $^{[1]}$		
1,1,1,2-tetrafluoroethane		Skin: adverse effect observed (irritating) $^{[1]}$		
		Skin: no adverse effect observed (not irritating) $^{\left[1\right]}$		
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute to	oxicity 2. Value obtained from manufacturer's SDS. Unless otherwise		
	specified data extracted from RTECS - Register of Toxic Effect of chemi	ical Substances		
1,1,1-TRIFLUOROETHANE	NOTE: Substance has been shown to be mutagenic in at least one ass cellular DNA.	ray, or belongs to a family of chemicals producing damage or change to		
PENTAFLUOROETHANE	Cardiac sensitisation threshold limit >245400 mg/m3 Anaesthetic effo	ects threshold limit 490800 mg/m3 * DuPont SDS		
1,1,1,2-TETRAFLUOROETHANE	* with added oxygen - ZhongHao New Chemical Materials MSDS Exce concentrations of decomposition products can cause lung oedema. Disinfection by products (DBPs) re formed when disinfectants such as	•		

health effects of DBPs. To date, several hundred DBPs have been identified.

Version No: **10.1** Page **8** of **11**

R404A

Issue Date: **28/05/2024**Print Date: **02/07/2024**

Numerous haloalkanes and haloalkenes have been tested for carcinogenic and mutagenic activities. n general, the genotoxic potential is dependent on the nature, number, and position of halogen(s) and the molecular size of the compound.

Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	×	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

Legend:

🗶 – Data either not available or does not fill the criteria for classification

✓ – Data available to make classification

SECTION 12 Ecological information

Toxicity

	Endpoint	Test Duration (hr)	Species	Value	Source
R404A	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
1,1,1-trifluoroethane	ECO(ECx)	96h	Algae or other aquatic plants	>44mg/l	2
	EC50	72h	Algae or other aquatic plants	~71mg/l	2
	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	>114mg/l	2
. 6	EC50	96h	Algae or other aquatic plants	142mg/l	2
pentafluoroethane	LC50	96h	Fish	>81.8mg/l	2
	NOEC(ECx)	96h	Fish	10mg/l	2
	EC50	48h	Crustacea	>97.9mg/l	2
	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	96h	Fish	300mg/l	Not Available
	EC50	96h	Algae or other aquatic plants	142mg/l	2
1,1,1,2-tetrafluoroethane	EC50	72h	Algae or other aquatic plants	>114mg/l	2
	EC50	48h	Crustacea	980mg/l	Not Available
	LC50	96h	Fish	450mg/l	Not Availabl
Legend:	Ecotox databa		Registered Substances - Ecotoxicological Informatio tic Hazard Assessment Data 6. NITE (Japan) - Bioc		

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
1,1,1-trifluoroethane	HIGH	HIGH
pentafluoroethane	HIGH	HIGH
1,1,1,2-tetrafluoroethane	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
1,1,1-trifluoroethane	LOW (LogKOW = 1.7393)
pentafluoroethane	LOW (LogKOW = 1.5472)
1,1,1,2-tetrafluoroethane	LOW (LogKOW = 1.68)

Mobility in soil

Issue Date: 28/05/2024 Print Date: 02/07/2024 R404A

Ingredient	Mobility
1,1,1-trifluoroethane	LOW (Log KOC = 48.64)
pentafluoroethane	LOW (Log KOC = 154.4)
1,1,1,2-tetrafluoroethane	LOW (Log KOC = 96.63)

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal

- Evaporate residue at an approved site.
- Pacturn empty containers to supplier. If containers are marked non-returnable establish means of disposal with manufacturer prior to purchase.
- Ensure damaged or non-returnable cylinders are gas-free before disposal.

SECTION 14 Transport information

Labels Required



Land transport (ADG)

14.1. UN number or ID number	3337			
14.2. UN proper shipping name	REFRIGERANT GAS R 404A			
14.3. Transport hazard class(es)	Class Subsidiary Hazard	2.2 Not Applicable		
14.4. Packing group	Not Applicable	Not Applicable		
14.5. Environmental hazard	Not Applicable			
14.6. Special precautions for user	Special provisions Limited quantity	Not Applicable 120 ml		

Air transport (ICAO-IATA / DGR)

14.1. UN number	3337			
14.2. UN proper shipping name	Refrigerant gas R 404A			
14.3. Transport hazard	ICAO/IATA Class	2.2		
class(es)	ICAO / IATA Subsidiary Hazard	Not Applicable		
	ERG Code	2L		
14.4. Packing group	Not Applicable			
14.5. Environmental hazard	Not Applicable			
	Special provisions		Not Applicable	
	Cargo Only Packing Instructions		200	
	Cargo Only Maximum Qty / Pack		150 kg	
14.6. Special precautions for user	Passenger and Cargo Packing Instructions		200	
	Passenger and Cargo Maximum Qty / Pack		75 kg	
	Passenger and Cargo Limited Qu	uantity Packing Instructions	Forbidden	
	Passenger and Cargo Limited Maximum Qty / Pack		Forbidden	

R404A

Issue Date: 28/05/2024 Page 10 of 11 Print Date: 02/07/2024

14.1. UN number	3337		
14.1. ON Humber	3337		
14.2. UN proper shipping name	REFRIGERANT GAS R 404A		
14.3. Transport hazard class(es)	IMDG Class	2.2	
	IMDG Subsidiary Hazard	Not Applicable	
14.4. Packing group	Not Applicable		
14.5 Environmental hazard	Not Applicable		
14.6. Special precautions for user	EMS Number F-	-C , S-V	
	Special provisions N	lot Applicable	
	Limited Quantities 12	20 mL	

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
1,1,1-trifluoroethane	Not Available
pentafluoroethane	Not Available
1,1,1,2-tetrafluoroethane	Not Available

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
1,1,1-trifluoroethane	Not Available
pentafluoroethane	Not Available
1,1,1,2-tetrafluoroethane	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

1,1,1-trifluoroethane is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

pentafluoroethane is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

1,1,1,2-tetrafluoroethane is found on the following regulatory lists

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 4

Australian Inventory of Industrial Chemicals (AIIC)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

Additional Regulatory Information

Not Applicable

National Inventory Status

National Inventory	Status	
Australia - AIIC / Australia Non- Industrial Use	Yes	
Canada - DSL	Yes	
Canada - NDSL	No (1,1,1-trifluoroethane; pentafluoroethane; 1,1,1,2-tetrafluoroethane)	
China - IECSC	Yes	
Europe - EINEC / ELINCS / NLP	Yes	
Japan - ENCS	Yes	
Korea - KECI	Yes	
New Zealand - NZIoC	Yes	
Philippines - PICCS	Yes	

R404A

Issue Date: **28/05/2024**Print Date: **02/07/2024**

National Inventory	Status	
USA - TSCA	Yes	
Taiwan - TCSI	Yes	
Mexico - INSQ	Yes	
Vietnam - NCI	Yes	
Russia - FBEPH	Yes	
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.	

SECTION 16 Other information

Revision Date	28/05/2024
Initial Date	26/11/2004

SDS Version Summary

Version	Date of Update	Sections Updated
9.1	23/12/2022	Classification review due to GHS Revision change.
10.1	28/05/2024	Hazards identification - Classification, Handling and storage - Storage (suitable container)

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

- PC TWA: Permissible Concentration-Time Weighted Average
- ▶ PC STEL: Permissible Concentration-Short Term Exposure Limit
- ▶ IARC: International Agency for Research on Cancer
- ▶ ACGIH: American Conference of Governmental Industrial Hygienists
- ▶ STEL: Short Term Exposure Limit
- ► TEEL: Temporary Emergency Exposure Limit。
- IDLH: Immediately Dangerous to Life or Health Concentrations
- ES: Exposure Standard
- OSF: Odour Safety Factor
- ▶ NOAEL: No Observed Adverse Effect Level
- ▶ LOAEL: Lowest Observed Adverse Effect Level
- ► TLV: Threshold Limit Value
- LOD: Limit Of Detection
- ▶ OTV: Odour Threshold Value
- ▶ BCF: BioConcentration Factors
- ▶ BEI: Biological Exposure Index
- ▶ DNEL: Derived No-Effect Level
- ▶ PNEC: Predicted no-effect concentration
- AIIC: Australian Inventory of Industrial Chemicals
- DSL: Domestic Substances List
- NDSL: Non-Domestic Substances List
- ▶ IECSC: Inventory of Existing Chemical Substance in China
- ▶ EINECS: European INventory of Existing Commercial chemical Substances
- ▶ ELINCS: European List of Notified Chemical Substances
- NLP: No-Longer Polymers
- ▶ ENCS: Existing and New Chemical Substances Inventory
- ▶ KECI: Korea Existing Chemicals Inventory
- NZIoC: New Zealand Inventory of Chemicals
- ▶ PICCS: Philippine Inventory of Chemicals and Chemical Substances
- ► TSCA: Toxic Substances Control Act
- ▶ TCSI: Taiwan Chemical Substance Inventory
- ▶ INSQ: Inventario Nacional de Sustancias Químicas
- ▶ NCI: National Chemical Inventory
- FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances